

Application: Constructed with the exclusive PVC double helix for superior flexibility, abrasion resistance and low coefficient of friction. Lightweight in construction, it is designed for handling the majority of common industrial chemicals under pressure, gravity flow, or medium suction service.

Construction:

Tube: Black conductive pliosyn UHMWPE
Cover: Yellow chemivic with double orange pliovic outer helix (antistatic wires are inside the pliovic helixes)
Reinforcement: Spiral-plied synthetic fabric

Temperature Range: -40°F to 160°F (-40°C to 71°C)

Branding:

Continental **ContiTech** **INFINITY**™ CHEMICAL HOSE 150 PSI **CAUTION:** HOSE AND COUPLINGS SHOULD BE INSPECTED PRIOR TO EACH USE. USE OF DAMAGED ASSEMBLY COULD BE HAZARDOUS #### MADE IN CANADA

Packaging: 100' lengths, coiled and polywrapped

Couplings: Use Continental ContiTech Insta-Lock™ Cam & Groove Fittings with this product. See the Coupling Systems. Information pages at the back of the Industrial Hose Product Catalog.

Order Code: 546-171

Order Code	Size	I.D.		O.D.		W.P.		B.R.		Vacuum HG		Weight	
	(in)	(in)	(mm)	(in)	(mm)	(PSI)	(MPa)	(in)	(mm)	(in)	(mm)	(Lb/ft)	(Kg/m)
546171064	2	2.000	50.8	2.79	70.9	150	1.03	12	305	23	584	1.22	1.81
546171107	3	3.000	76.2	3.81	96.7	150	1.03	18	457	23	584	1.73	2.56
546171123	4	4.000	101.6	4.83	122.7	150	1.03	24	610	23	584	2.32	3.44

Revised January 2017